

Safety Data Sheet

RESINA DOLPHON CR-1034

Safety Data Sheet dated 28/9/2016, version 2



SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Mixture identification:

Trade name: RESINA DOLPHON CR-1034
Trade code: 351318

1.2. Relevant identified uses of the substance or mixture and uses advised against: electroinsulating resin for industrial use only

1.3. Details of the supplier of the safety data sheet

Company:

ALBESIANO SISA Vernici S.r.l. - Società con unico socio
Via Rigolfo 73 - 10028 - Trofarello (TO) - Italia
Tel: +39/0116493111
Fax: +39/0116493112

Competent person responsible for the safety data sheet:

Giovanni Rocco - info.albesiano@vonroll.com

1.4. Emergency telephone number:

Tel: +390116493111 (h. 8/12 ÷ 13/17 italian time)
Fax: +390116493112

"National Poisons Information Service (Birmingham Unit)

City Hospital
Dudley Rd - Birmingham





Tel: 844 892 0111

mail@npis.org"

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

EC regulation criteria 1272/2008 (CLP)

-  Warning, Eye Irrit. 2, Causes serious eye irritation.
-  Warning, Skin Irrit. 2, Causes skin irritation.
-  Warning, Skin Sens. 1, 1A, 1B, May cause an allergic skin reaction.
-  Aquatic Chronic 2, Toxic to aquatic life with long lasting effects.

Adverse physicochemical, human health and environmental effects:

No other hazards

2.2. Label elements

Hazard pictograms:



351318/2 (1272/2008/EC)

Page n. 1 of 8

Safety Data Sheet

RESINA DOLPHON CR-1034

Warning

Hazard statements:

- H319 Causes serious eye irritation.
- H315 Causes skin irritation.
- H317 May cause an allergic skin reaction.
- H411 Toxic to aquatic life with long lasting effects.

Precautionary statements:

- P101 If medical advice is needed, have product container or label at hand.
- P102 Keep out of reach of children.
- P103 Read label before use.
- P280 Wear protective gloves/protective clothing/eye protection/face protection.
- P501 Dispose of contents/container in accordance with applicable regulations.

Special Provisions:

None

Special provisions according to Annex XVII of REACH and subsequent amendments:

None

2.3. Other hazards

vPvB Substances: None - PBT Substances: None

Other Hazards:

No other hazards

SECTION 3: Composition/information on ingredients

3.1. Substances





N.A.

3.2. Mixtures

Hazardous components within the meaning of CLP regulation and related classification:

>= 40% - < 50% reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight <= 700)

REACH No.: 01-2119456619-26, Index number: 603-074-00-8, CAS: 25068-38-6, EC: 500-033-5

-  3.2/2 Skin Irrit. 2 H315
-  3.4.2/1 Skin Sens. 1 H317
-  3.3/2 Eye Irrit. 2 H319
-  4.1/C2 Aquatic Chronic 2 H411

SECTION 4: First aid measures

4.1. Description of first aid measures

In case of skin contact:

- Immediately take off all contaminated clothing.
- Areas of the body that have - or are only even suspected of having - come into contact with the product must be rinsed immediately with plenty of running water and possibly with soap.
- Wash thoroughly the body (shower or bath).
- Remove contaminated clothing immediately and dispose off safely.
- After contact with skin, wash immediately with soap and plenty of water.

In case of eyes contact:

- After contact with the eyes, rinse with water with the eyelids open for a sufficient length of time, then consult an ophthalmologist immediately.
- Protect uninjured eye.

Safety Data Sheet

RESINA DOLPHON CR-1034

In case of Ingestion:

Do not under any circumstances induce vomiting. OBTAIN A MEDICAL EXAMINATION IMMEDIATELY.

In case of Inhalation:

Remove casualty to fresh air and keep warm and at rest.

4.2. Most important symptoms and effects, both acute and delayed

None

4.3. Indication of any immediate medical attention and special treatment needed

In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible).

Treatment:

None

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media:

Water.

Carbon dioxide (CO₂).

Extinguishing media which must not be used for safety reasons:

None in particular.

5.2. Special hazards arising from the substance or mixture

Do not inhale explosion and combustion gases.

Burning produces heavy smoke.

5.3. Advice for firefighters

Use suitable breathing apparatus .

Collect contaminated fire extinguishing water separately. This must not be discharged into drains.

Move undamaged containers from immediate hazard area if it can be done safely.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Wear personal protection equipment.

Remove persons to safety.

See protective measures under point 7 and 8.

6.2. Environmental precautions

Do not allow to enter into soil/subsoil. Do not allow to enter into surface water or drains.

Retain contaminated washing water and dispose it.

In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities.

Suitable material for taking up: absorbing material, organic, sand

6.3. Methods and material for containment and cleaning up

Wash with plenty of water.

6.4. Reference to other sections

See also section 8 and 13

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Avoid contact with skin and eyes, inhalation of vapours and mists.

Don't use empty container before they have been cleaned.

Before making transfer operations, assure that there aren't any incompatible material residuals in the containers.

Contaminated clothing should be changed before entering eating areas.

Do not eat or drink while working.

See also section 8 for recommended protective equipment.

7.2. Conditions for safe storage, including any incompatibilities

Keep away from food, drink and feed.

Incompatible materials:

351318/2 (1272/2008/EC)

Page n. 3 of 8

Safety Data Sheet

RESINA DOLPHON CR-1034

None in particular.

Instructions as regards storage premises:

Adequately ventilated premises.

7.3. Specific end use(s)

None in particular

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

None

DNEL Exposure Limit Values

reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight \leq 700) -

CAS: 25068-38-6

Worker Industry: 8.33 mg/kg - Exposure: Human Dermal - Frequency: Short Term, systemic effects

Worker Industry: 12.25 03 - Exposure: Human Inhalation - Frequency: Short Term, systemic effects

Worker Industry: 8.33 mg/kg - Exposure: Human Dermal - Frequency: Long Term, systemic effects

Worker Industry: 12.25 03 - Exposure: Human Inhalation - Frequency: Long Term, systemic effects

Consumer: 3.571 mg/kg - Exposure: Human Dermal - Frequency: Short Term, systemic effects

Consumer: 0.75 mg/kg - Exposure: Human Oral - Frequency: Short Term, systemic effects

Consumer: 3.571 mg/kg - Exposure: Human Dermal - Frequency: Long Term, systemic effects

Consumer: 0.75 mg/kg - Exposure: Human Oral - Frequency: Long Term, systemic effects

PNEC Exposure Limit Values

reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight \leq 700) -

CAS: 25068-38-6

Target: Fresh Water - Value: 0.006 mg/l

Target: Marine water - Value: 0.0006 mg/l

Target: Water, intermittent release - Value: 0.018 mg/l

Target: STP Microorganisms - Value: 10 mg/l

Target: Freshwater sediments - Value: 0.996 mg/l

Target: Marine water sediments - Value: 0.0996 mg/l

Target: Soil (agricultural) - Value: 0.196 mg/l

8.2. Exposure controls

Eye protection:

Use close fitting safety goggles, don't use eye lens.

Protection for skin:

Use clothing that provides comprehensive protection to the skin, e.g. cotton, rubber, PVC or viton.

Protection for hands:

Use protective gloves that provides comprehensive protection, e.g. P.V.C., neoprene or rubber.

Respiratory protection:

Not needed for normal use.

Thermal Hazards:

None

Environmental exposure controls:

None

Appropriate engineering controls:

None

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance and colour: Thixotropic - red

Odour: Characteristic

Odour threshold: N.A.

Initial boiling point and boiling range: N.A.

Solid/gas flammability: N.A.

Upper/lower flammability or explosive limits: N.A.

351318/2 (1272/2008/EC)

Page n. 4 of 8

Safety Data Sheet

RESINA DOLPHON CR-1034

Vapour density:	N.A.	
Flash point:	>150 °C	
Evaporation rate:	N.A.	
Vapour pressure:	N.A.	
Relative density:	>= 1500	<= 1550 g/l
Solubility in water:	N.A.	
Solubility in oil:	N.A.	
Partition coefficient (n-octanol/water):	N.A.	
Auto-ignition temperature:	N.A.	
Decomposition temperature:	N.A.	
Viscosity:	N.A.	
Oxidizing properties:	N.A.	

9.2. Other information

Miscibility:	N.A.
Fat Solubility:	N.A.
Conductivity:	N.A.
Substance Groups relevant properties	N.A.

SECTION 10: Stability and reactivity

- 10.1. Reactivity
Stable under normal conditions
- 10.2. Chemical stability
Stable under normal conditions
- 10.3. Possibility of hazardous reactions
It may catch fire on contact with powerful oxidising agents.
- 10.4. Conditions to avoid
Stable under normal conditions.
- 10.5. Incompatible materials
None in particular.
- 10.6. Hazardous decomposition products
None.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Toxicological information of the mixture:

N.A.

Toxicological information of the main substances found in the mixture:

reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight <= 700) -

CAS: 25068-38-6

a) acute toxicity:

Test: LD50 - Route: Oral - Species: Rat > 15.000 mg/kg

Test: LD50 - Route: Skin - Species: Rabbit = 23.000 mg/kg

Liquid epoxy resin contained in this material causes only minor skin irritation. However, all epoxy resins are capable of causing sensitizing of the skin. Susceptibility to skin irritation and sensitization varies from person to person.

In a sensitized individual the allergic dermatitis may not appear until after several days or weeks of frequent and prolonged contact. Therefore, even though the skin irritation potential is slight, skin contact should be avoided.

Once sensitization has occurred, exposure of the skin to very small quantities of the material may cause erythema and edema.

If not differently specified, the information required in Regulation 453/2010/EC listed below must be considered as N.A.:

a) acute toxicity;

b) skin corrosion/irritation;

351318/2 (1272/2008/EC)

Page n. 5 of 8

Safety Data Sheet

RESINA DOLPHON CR-1034

- c) serious eye damage/irritation;
- d) respiratory or skin sensitisation;
- e) germ cell mutagenicity;
- f) carcinogenicity;
- g) reproductive toxicity;
- h) STOT-single exposure;
- i) STOT-repeated exposure;
- j) aspiration hazard.

SECTION 12: Ecological information

12.1. Toxicity

Adopt good working practices, so that the product is not released into the environment.

Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight \leq 700) -

CAS: 25068-38-6

a) Aquatic acute toxicity:

Endpoint: LC50 - Species: Fish = 2 mg/l - Duration h: 96

Endpoint: EC50 - Species: Daphnia = 1.8 mg/l - Duration h: 48

Endpoint: ErC50 - Species: water plants = 11 mg/l - Duration h: 72

12.2. Persistence and degradability

None

N.A.

12.3. Bioaccumulative potential

N.A.

12.4. Mobility in soil

N.A.

12.5. Results of PBT and vPvB assessment

vPvB Substances: None - PBT Substances: None

12.6. Other adverse effects

None

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Recover if possible. In so doing, comply with the local and national regulations currently in force.

SECTION 14: Transport information

14.1 UN number:

UN number: 3082

14.2 UN proper shipping name:

Environmentally Hazardous Substance, Liquid, N.o.s., (Blend of diallyl phthalate)

14.3 Transport hazard class(es):

Road (ADR): 9

Air (ICAO/IATA): 9

Sea (IMO): IMCO CLASS 9 - UN 3082
EmS: F-A, S-F

14.4 Packing Group:

III

14.5 Environmental hazards

Marine pollutant: Yes (diallyl phthalate)

351318/2 (1272/2008/EC)

Page n. 6 of 8

vonRoll

ALBESIANO SISA vernici S.r.l. - Società con unico socio
Via Rigolfo, 73 - 10028 Trofarello (TO) - Italia
Tel: +39/0116493111 - Fax: +39/0116493112 - E-mail: info.albesiano@vonroll.com
Licenziataria per la produzione delle vernici e resine elettroisolanti DOLPH'S



EST. 1910

Safety Data Sheet

RESINA DOLPHON CR-1034

14.6 Special Precautions for User
ADR-Tunnel Restriction Code: (E)

14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code
No

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture
Dir. 67/548/EEC (Classification, packaging and labelling of dangerous substances)
Dir. 99/45/EC (Classification, packaging and labelling of dangerous preparations)
Dir. 98/24/EC (Risks related to chemical agents at work)
Dir. 2000/39/EC (Occupational exposure limit values)
Dir. 2006/8/EC

Regulation (EC) n. 1907/2006 (REACH)

Regulation (EC) n. 1272/2008 (CLP)

Regulation (EC) n. 790/2009 (ATP 1 CLP) and (EU) n. 758/2013

Regulation (EU) n. 453/2010 (Annex II)

Regulation (EU) n. 286/2011 (ATP 2 CLP)

Restrictions related to the product or the substances contained according to Annex XVII Regulation (EC) 1907/2006 (REACH) and subsequent modifications:

Restrictions related to the product:

Restriction 3

Restriction 40

Restrictions related to the substances contained:

No restriction.

Where applicable, refer to the following regulatory provisions :

Directive 2012/18/EU ('Activities linked to risks of serious accidents') and subsequent amendments.

Regulation (EC) nr 648/2004 (detergents).

1999/13/EC (VOC directive)

Provisions related to directive 2012/18/EU (Seveso III):
E2

15.2. Chemical safety assessment
No

SECTION 16: Other information

Full text of phrases referred to in Section 3:

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H319 Causes serious eye irritation.

H411 Toxic to aquatic life with long lasting effects.

This document was prepared by a competent person who has received appropriate training.

Main bibliographic sources:

ECDIN - Environmental Chemicals Data and Information Network - Joint Research Centre, Commission of the European Communities

SAX's DANGEROUS PROPERTIES OF INDUSTRIAL MATERIALS - Eight Edition - Van Nostrand Reinold

CCNL - Appendix 1

Insert further consulted bibliography

The information contained herein is based on our state of knowledge at the above-specified date. It refers solely to the product indicated and constitutes no guarantee of particular quality.
It is the duty of the user to ensure that this information is appropriate and complete with respect to the specific use intended.

351318/2 (1272/2008/EC)

Page n. 7 of 8

Safety Data Sheet

RESINA DOLPHON CR-1034

This MSDS cancels and replaces any preceding release.

ADR:	European Agreement concerning the International Carriage of Dangerous Goods by Road.
CAS:	Chemical Abstracts Service (division of the American Chemical Society).
CLP:	Classification, Labeling, Packaging.
DNEL:	Derived No Effect Level.
EINECS:	European Inventory of Existing Commercial Chemical Substances.
GefStoffVO:	Ordinance on Hazardous Substances, Germany.
GHS:	Globally Harmonized System of Classification and Labeling of Chemicals.
IATA:	International Air Transport Association.
IATA-DGR:	Dangerous Goods Regulation by the "International Air Transport Association" (IATA).
ICAO:	International Civil Aviation Organization.
ICAO-TI:	Technical Instructions by the "International Civil Aviation Organization" (ICAO).
IMDG:	International Maritime Code for Dangerous Goods.
INCI:	International Nomenclature of Cosmetic Ingredients.
KSt:	Explosion coefficient.
LC50:	Lethal concentration, for 50 percent of test population.
LD50:	Lethal dose, for 50 percent of test population.
LTE:	Long-term exposure.
PNEC:	Predicted No Effect Concentration.
RID:	Regulation Concerning the International Transport of Dangerous Goods by Rail.
STE:	Short-term exposure.
STEL:	Short Term Exposure limit.
STOT:	Specific Target Organ Toxicity.
TLV:	Threshold Limiting Value.
TWATLV:	Threshold Limit Value for the Time Weighted Average 8 hour day. (ACGIH Standard).
WGK:	German Water Hazard Class.